


The name AIRSTOP® says it all. Michelin®  
high-performance aircraft inner tubes.

AIRSTOP MICHELIN  
167 (Type III) Valve TR  
5.00-5 P/N:092-308-0



Copyright © 2007 MATC, LLC. All rights reserved.

Michelin® AIRSTOP® aircraft inner tubes are designed to provide the same level of performance aviators have come to expect from Michelin® tires. They're built to provide dependable air retention over a full range of operating conditions, and they're compatible with most tire brands.



# Michelin® AIRSTOP® Aircraft Inner Tubes.



(Typical AIRSTOP® inner tube shown)

## Key Product Features and Benefits

① Advanced Butyl Material	Exclusive Michelin butyl compound offers excellent resistance to diffusion for extended air retention and dependable performance. AIRSTOP® tubes help provide the same high quality seal found in Michelin® AIR X® radial tires.
② Circular Extrusion Manufacturing Process	A Michelin exclusive, AIRSTOP® tubes are formed without a circumferential splice, resulting in fewer joints and a more uniform tubewall thickness after inflation. This helps provide optimized reliability at a minimal weight.
③ Built-In Balance	All AIRSTOP® tubes are manufactured to exacting balance tolerances (without correction), which meet or exceed all industry standards. This eliminates the need to further balance the wheel assembly in order to compensate for balance irregularities in the tube.
④ Easy Installation	Tube lubricant is factory applied to the tube exterior for easier installation and to help minimize foldover after installation and inflation. In addition, molded vent ridges help channel trapped air back to the valve stem for easy release.
⑤ Low Temperature Performance	AIRSTOP® tubes are designed to perform in the extreme low operating temperature of minus 48 degrees C, so you can confidently fly in cold weather with consistent, reliable performance.

Size	Valve	Part No.	Wt. (lbs)
355x150-4	AC-5 / Bent 90 degrees	097-543-0	1.0
5.00-4	TR-67 / Bent 90 degrees	097-300-0*	0.9
5.00-5	TR-67A / Bent 90 degrees	092-308-0	0.9
15x6.0-6	TR-20 / Straight	097-500-0	1.2
15x6.0-6 (H60TW)	TR-67 / Bent 90 degrees	092-501-0	1.3
6.00-6	TR-20 / Straight	092-315-0	1.4
17.5x6.25-6	TR-20 / Straight	092-315-0	1.4
7.00-6	TR-20 / Straight	092-318-0	1.6
8.00-6	TR-20 / Straight	092-318-0	1.6
6.50-8	TR-15 / Straight	092-337-0	1.9

Size	Valve	Part No.	Wt. (lbs)
7.00-8	TR-15 / Straight	092-337-0	1.9
22x8.0-8	TR-15 / Straight	097-534-0*	2.5
6.50-10	TR-25 / Straight	092-344-0	1.9
7.50-10	TR-25 / Straight	097-373-0	2.8
8.50-10	TR-25 / Straight	092-348-0	2.8
7.50-14	TR-176A / Bent 60 degrees	097-360-0*	4.0
11.00-12	TR-13 / Straight	092-354-0*	5.6
8.90x12.5	TR-15 / Straight	097-383-0*	4.7
12.50-16	TR-101 / Bent 90 degrees	097-368-0*	9.2
27"	TR-25 / Straight	097-150-0*	5.9

\* Limited production. Specifications subject to change without notice.

**Michelin Aircraft Tyre**  
23 Place des Carmes  
63040 Clermont-Ferrand  
France  
Tel 33.4.73.32.76.40  
Fax 33.4.73.32.76.42

**Michelin Aircraft Tire Company, LLC**  
One Parkway South  
Greenville, SC 29615 USA  
Tel 864.458.5000  
Fax 864.458.6746

**Michelin Australia Pty Ltd**  
Unit 35/24 Anzac Avenue  
Smeaton Grange  
NSW 2567, Australia  
Tel 61.2.4648.8202  
Fax 6.12.4646.1949

[www.airmichelin.com](http://www.airmichelin.com)

